



features



Double wall
drawer



Full
Extension



Concealed Slides
Side Mount



Soft
Close



Push-to-Open
(Optional)

advantages

- Tool free front and gallery rail fixings come standard
- Runners and slides are concealed, giving the drawer a cleaner look
- Side adjustment is accessed from the right profile only
- Built in soft closing mechanism
- Fully synchronised soft close drawer and no knocking noise
- 2D adjustment on standard drawer (side and height)
- 3D adjustment on pot drawers (side, height and tilt adjustment through the gallery rail)

- Optimal soft closing operation
- Load capacity 40kg
- White finish
- Full extension synchronised drawer
- Tool-free assembly and removal of drawer
- Double wall drawer
- 2-dimensional front adjustment
Up/down adjustment ± 2 mm
(access from left and right profile)
Left/right adjustment ± 1.5 mm
(access from right profile only)

Nominal Length	Soft Closing				Push-to-Open	
	Profile			Medium	High Pot Drawer	Profile
	68 mm	83 mm	115 mm	135 mm	199 mm	83 mm
	Set A	Set A	Set A	Set B	Set D	Set A
270mm		B01270A	B02270A			
300mm		B01300A	B02300A			B513004A
350mm		B01350A	B02350A	B01350B	B01350D	B513504A
400mm		B01400A	B02400A	B01400B	B01400D	B514004A
450mm		B01450A	B02450A	B01450B	B01450D	B514504A
500mm		B01500A	B02500A	B01500B	B01500D	B515004A
550mm		B01550A	B02550A	B01550B	B01550D	B515504A
600mm		B01600A	B02600A	Use Set B components	Use Set D components	

Set A - Comes complete drawer with easy fix front brackets Set B - Set A (83mm) plus easy fix gallery rails & medium back brackets Set D - Set A (83mm) plus easy fix gallery rails & high back brackets.

115mm - Optional medium pot drawer will require additional 167mm back bracket and easy fix gallery rail.

*Synchronisation Rod (M0FH02) is needed for drawers with width of 600mm or wider for Push-to-Open mechanism to work.

68mm height- B00 63mm Profile				135mm height- B01 83mm Profile			
Space requirement in cabinet	Front installation dimensions	Front drilling dimension	Back installation dimensions	Space requirement in cabinet	Front installation dimensions	Front drilling dimension	Back installation dimensions
83mm height-B01 83mm Profile				167mm height-B02 115mm Profile			
Space requirement in cabinet	Front installation dimensions	Front drilling dimension	Back installation dimensions	Space requirement in cabinet	Front installation dimensions	Front drilling dimension	Back installation dimensions
Inner drawer: 103.5 							
115mm height- B02 115mm Profile				199mm height- B01 83mm Profile			
Space requirement in cabinet	Front installation dimensions	Front drilling dimension	Back installation dimensions	Space requirement in cabinet	Front installation dimensions	Front drilling dimension	Back installation dimensions
Inner drawer: 134 							

DTC INSTALLATION

Installation Instruction

Back assembly

Click

Click

Bottom assembly

Fix screws

Front assembly

Click

Adjustment

Left & right adjustment

Up & down adjustment

Slide into the cabinet

Press-in

Removal

Tip up the cover and pull out

Turn screw driver to release the drawer front

Lift the release handle and out Pull the drawer

Standard Drawer- 68, 83 & 115 mm (B01 & B02 series)

Front assembly

Medium Pot Drawer- 135 & 167 mm (B01 & B02 series)

Front assembly

Back assembly

Fit the front

High Pot Drawer- 199 mm (B01 series) with double gallery rail option

Back assembly

Fit the front

High Pot Drawer Installation with side wings

Side assembly

Side assembly

Standard Drawer Inner Drawer Installation

Front assembly

High Pot Drawer Inner Drawer Installation with double box side

Fit the front

Front assembly

Side assembly

Push to open trigger range

1/3 1/3 1/3

✗ ✓ ✗